

STK400 構造用鋼管

外径	肉 厚								5.5m	6m	12m
	1.9	2.3	2.8	3.2	3.5	3.8	4.2	4.5			
21.7	1.9	2.3	2.8						○	○	
27.2	1.9	2.3	2.8						○	○	
34.0	2.3	3.2							○	○	
42.7	2.3	2.8	3.2	3.5					○	○	
48.6	2.3	3.2	3.5						○	○	
60.5	2.3	2.8	3.2	3.8	5.5				○	○	○
76.3	2.8	3.2	4.2	7.0						○	○
89.1	2.8	3.2	4.2	5.5	7.6					○	○
101.6	3.2	4.2	5.7	8.1						○	○
114.3	3.5	4.5	6.0	8.6						○	○
139.8	3.5	4.5	6.0	6.6	9.5					○	○
165.2	3.7	4.5	5.0	6.0	7.1	9.3	11.0			○	○
190.7	4.5	5.3	6.0	7.0						○	○
216.3	4.5	5.8	6.0	7.0	8.2	10.3	12.7			○	○
241.8	6.2									○	○
267.4	4.5	6.0	6.6	9.3	12.7	15.1				○	○
318.5	6.0	6.9	7.9	9.0	9.5	10.3	12.7	14.3	17.4	○	○
355.6	6.4	7.9	9.5	11.1	12.7	16.0	19.0	22.0		○	○
406.4	6.4	7.9	9.5	12.7	16.0	19.0	22.0			○	○
457.2	6.4	7.9	9.5	12.7	16.0	19.0				○	○
508.0	6.4	7.9	9.5	12.7	16.0	19.0	22.0			○	○
558.8	6.4	7.9	9.5	12.7	16.0	19.0	22.0			○	○
609.6	6.4	7.9	9.5	12.7	16.0	19.0	22.0			○	○